

GAFGLAS[®] Ply 4



Description

GAFGLAS Ply 4 roofing felt is constructed with a strong glass fiber mat that is coated with the finest quality asphalt, and is designed with optimum porosity to assure a sound, watertight membrane.

Uses

GAFGLAS Ply 4 is used as a ply felt in the construction of built-up roofs. It is designed for use in all climatic zones and is appropriate for use as a base sheet, as a ply felt, and in the construction of flashing membranes.

Advantages

- High tensile strength and a high degree of dimensional stability, resulting in a roof system with greater resistance to splitting and cracking.
- Optimum porosity of the felt provides ready escape of air while allowing proper asphalt penetration at the time of mopping.
- Asphalt coating provides high degree of moisture resistance.
- Fire resistant—for use in UL Class A rated assemblies.
- Wind uplift resistance—selected roofing assemblies with GAFGLAS Ply 4 felts meet FMRC Class 1-180 when installed over concrete decks.
- Meets ASTM D-2178, Type IV specifications.
- Meets requirements for application in all climatic zones.
- Rolls out flat for easy installation.

Applicable Standards

- UL Approved for use in the construction of Class A, B, or C roofs (Type G1 BUR)
- FM Approved
- ASTM D-2178, Type IV
- New York City MEA 78-89 Gravel Surfaced Systems 96-89 Smooth Surf. Systems
- Dade County Product Approval

Product Data (Approximate)

Roll Size.....	39.4" x 161.8'
	(1.0m x 49.3m)
Coverage Per Roll.....	5 squares
Roll Weight.....	40 lbs. (18.2 kg)

